Speed Queen.

Multi-Housing

Micro Display Control

SSEY17 (elec) SSGY19 (gas)



Commercial Heavy Duty Stack Dryer

Description

- · Four heat / cycle selections
- · Strong box meter case security
- Factory installed set at 45 minutes
- 1/3 HP motor; 120/60/1 15 amp
- Two separate controls allow two dryers in the space of one to operate independently
- · Control graphic arrows indicate upper and lower dryer
- Micro-display CARD operated control
 - Vend price programmable
 - Time countdown
 - Non-resettable cycle counter
- · Touch pad control
 - Sound annunciator



Features & Benefits

- Extra large 7.0 cu. ft., 18 lb. capacity galvanized steel cylinder.
- Wide door opening of 2.06 sq. ft. is the industry largest, offering residents easy loading and unloading.
- 100% serviceable from the front.



- Efficient dryer heating.
- 25,000 BTU (gas models)
- 5,350 watts (electric models)
- High efficiency exhaust blower with superior airflow of 220 cfm.
- Up-front lint filter is easy to clean and secured.
- Space-saving narrow cabinet (26-7/8 wide).



Specifications

Model	SSEY17 (elec) SSGY19 (gas)
Width - in. (mm)	26 7/8" (683)
Depth - in. (mm)	28" (711)
Height - in. (mm)	76 5/8" (1,946)
Cylinder Volume Capacity) - cu. ft. (liters)	7.0 (198)
Btu Per Hour - (kcal)	25,000 (6,300)
Heating Element	5,350 W 240 V (also 4,750 W 208 V)
Type of Gas (gas models only)	Factory-equipped Natural / Mixed Gas Convertible To LP Gas+
Utility Connections - in. (mm)	Gas: 3/8" NPT (9.5)
Air Outlet Diameter - in. (mm)	4" (102)
Exhaust Airflow	220 (105 liters/sec)
Maximum Exhaust Static Back Pressure	0.6" W.C.
Electrical Specifications Circuit Requirements	Gas 120/60/1 - 15 amp Elec 120/240/60/1 - 30 amp
Colors	White
Net Weight - Ibs. (kg)	Gas 275 (125) Elec 265 (120)
Shipping Weight - Ibs. (kg)	Gas 290 (132) Elec 280 (127)
Code Standard	Gas CSA Star Elec Underwriters Laboratories

Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at all Alliance Laundry Systems facilities have been awarded ISO 9001 certification. Features and certifications may vary by model.

At Speed Queen, we're confident that our heavy duty commercial washers and dryers are built better to last longer, that we're offering the following limited warranty to prove it. (+Parts only. Labor not included. See Speed Queen Warranty Bond for specifics.)

• Through three years+

a. Any part of the washer, single and stack dryer or stack washer/dryer.

• Through five years+

- a. Top load washer transmission assembly.
- b. Base and cabinet assembly including top, lid and door, against rust from inside out.

a. Stainless steel wash tub (top load washer) or stainless steel inner cylinder (front load washer).

	Medium	155°
← 23.5" (59.7 cm) →	High	160°
7.0" (17.8 cm) NOTE: ONE SEPAELECTRIC CORD DRYER UNIT		
4.0" (19.6 cm) (19.6 cm) (19.6 cm) (20.2 cm) (
	Spe	ed Que

Temperature Selection

Setting

115°

145°

Temperature

Delicate

Low